



FLEXIBLE METAL HOSES

FOR NATURAL GAS AND GPL

ACCORDING TO THE EN 14800:2007 FOR THE
CONNECTION OF THE DOMESTIC APPLIANCES



EN 14800



THE FLEXIBLE METAL HOSE



FOR NATURAL GAS AND GPL



ACCORDING TO THE EN 14800:2007 FOR THE CONNECTION OF THE DOMESTIC APPLIANCES

The corrugated metal hose is according to the EN 14800:2007 for the connection of the domestic appliances using natural gas and GPL.

AYVAZ N-GAS flexible metal hose assembly with nominal dimension DN8 and DN12 comply with European Standard EN 14800 and CE approved.

N-GAS is available in lengths of 500, 750, 1000, 1250, 1500 and 2000 mm.

MAIN FEATURES

- Metal Hose** : Corrugated metal hose in **AISI 316L (1.4404)** austenitic stainless steel as per EN ISO 10380.
- Braid** : Metal braid in AISI 304 (1.4301) austenitic stainless steel as per EN ISO 10380.
- Swivel Nuts** : Nut in **AISI 304 (1.4301)** as per ISO 228 G 1/2 thread or Ms58.
- Internal Parts** : Internal parts in AISI 304 (1.4301) austenitic stainless steel.
- Nipple** : Nipple in AISI 304 (1.4301) austenitic stainless steel as per ISO 7/1 R1/2 thread.
- External Coating** : Transparent PVC for the protection from household cleaners and other aggressive influences. And easy to clean.
- Gaskets** : NBR rubber according to the standard EN 549.



Length	NGAS Male / Female	NGAS Female / Female
	Art. Code	Art. Code
500 mm	701.150.151.050	701.150.152.050
750 mm	701.150.151.075	701.150.152.075
1000 mm	701.150.151.100	701.150.152.100
1250 mm	701.150.151.125	701.150.152.125
1500 mm	701.150.151.150	701.150.152.150
2000 mm	701.150.151.200	701.150.152.200

Ayvaz has rights to modify technical specifications without prior notification



info@ayvaz.com | www.ayvaz.com

