

# TYPE APPROVAL CERTIFICATE No. MAC056616XT

This is to certify that the product identified below satisfies the requirements of the standard quoted under "Reference standard"

Description Metallic expansion joints

Type AYVAZ Axial Expansion Joints PN2,5 to PN16 - DN25 to

DN1200

Applicant HACI AYVAZ ENDUSTRIYEL MAMULLER SAN. VE TIC.

A.S. - AYVAZ

Manufacturer HACI AYVAZ ENDUSTRIYEL MAMULLER SAN. VE TIC.

Place of manufacture A.S. - AYVAZ

ATATURK SANAYI BOLGESI, MUSTAFA INAN CAD.,

NO.36

34555 HADIMKOY, ISTANBUL

TURKEY

Reference standards RINA Rules for the Type Approval of Flexible Hoses and

**Expansion Joints** 

Issued in ISTANBUL on October 10, 2016. This Certificate is valid until October 9, 2021



RINA Services S.p.A. Volkan Celik

This certificate consists of this sheet plus an attachment

# MAC056616XT Attachment Page 1 0f 2

## 1. TECHNICAL CHARACTERISTICS

AYVAZ Axial Expansion Joints

## 1.1 Design Specifications

Size	DN 25 to DN 1200	DN 40 to DN 350	DN 50 to DIN 800
Working Pressure	PN2,5	PN 16	PN 2,5
Max. Working Temperature	600 °C	550 °C	550 °C
Axial movements	-20 / +10 mm	-40 /+20 mm	-40/+20 mm
Ends	Floating flange	Floating flange Welding end	Floating flange (PN 2,5 - PN 6) Flange (PN 10 - PN 16) / Welding end

#### 1.2 Materials

Bellow	14401 / 14404 / 1.4541	
Band	1.0038 / 14401 / 14404 / 1.4541	
Flange	1.0038	
Welding end	1.0038	

When other choices of materia<mark>ls are us</mark>ed per manu<mark>facturer's recommendations, the RINA agre<mark>emen</mark>t is to be obtained.</mark>

# 2. 2. REFERENCE DOCUMENTS

- Manufacturer's catalogue 1999 March Edition
- Drawings Nr 702.056.240.040 to 702.056.240.350 Expansion Joint PN 16 DN40-350
- Drawings Nr 702.056.210.050 to 702.056.210.800 Expansion Joint PN 2.5 DN 50-800
- Drawings Nr 702.036.213.050 to 702.056.213.800 Expansion Joint PN 2.5 DN50-800
- Drawings Nr 702.036.110.025 to 702.036.110.900, Nr 702.036.110.010 and 702.036.110.012 Expansion Joint PN 2.5 DN 25-1200

# 3. TEST REPORTS

- Type tests according to Testing Programme performed in-house,
- Pressure Impulse test, hydraulic pressure test, burst pressure test and cyclic expansion test,

## 4. FIELDS OF APPLICATION

- 4.1 The expansion joints may be used for the following service on board:
- Exhaust gas lines, Steam pressure lines
- Other marine class II and III piping systems according to the relevant requirements stated in Part C, Chapter 1, Sec 10 of RINA Rules
- 4.2 The use of floating flanges is only permitted for Class III water pipes and open-ended lines.
- 4.3 The use of stainless steel is to be restricted as per the requirements of RINA Rules.
- 4.4 Reduction factors are to be taken in consideration for maximum working pressure and tolerable movement caused by temperature influence according to manufacturer's recommendations.
- 4.5 The calculated maximum values of axial and/or lateral movements at 1000 full cycles are not to be exceeded.
- 4.6 The expansion joints are to be installed according to manufacturer's instructions and RINA Rules.
- 4.7 In case of high level of vibrations in the piping systems where fitted to engines pumps, compressors and other sources of high vibrations, care shall be taken in order to avoid that the natural frequency of compensator doesn't coincide with the system frequency.
- 4.8 The expansion joints must only be fitted in areas where they are always accessible

U

# Attachment Page 2 Of 2

## 5. ACCEPTANCE CONDITIONS

- 5.1 The products are to be supplied by HACI AYVAZ END. MAMULLER SAN. VE TIC. A.S. in compliance with the type and the requirements described in this certificate.
- 5.2 RINA product certificate is required.
- 5.3 Each expansion joint is to be hydraulic pressure tested to twice the maximum working pressure under witnessing of a Society's Surveyor when required by the Rules

# 6. MARKING OF PRODUCT

Each expansion joint shall be marked clearly to avoid any wrong utilization with

- Manufacturer's name or logo
- Type designation
- Date of manufacture
- Society's brand as relevant

This approval is given with the understanding that the manufacturer will accept full responsibility for informing shipbuilders or their sub-contractors of the proper methods of fitting and general maintenance of the products and of the conditions of this approval.

re