



# TKK-41&42

# THERMOSTATIC STEAM TRAPS

### GENERAL FEATURES

Ayvaz TKK-41 is suitable for corrosive medium especially sugar industry for ammoniac evacuation and it has also resistant to water hammer. It is impossible to clean TKK 41 because it is welded type however TKK-42 is suitable for cleaning.

Body, cover, filter are stainless steel.

The difference of TKK-42 is compact design and low condensate evacuation.

It is ideal for corrosive medium.

Ayvaz TKK-41 / TKK-42 should be assembled to the pipe line at horizontal position for working efficiently andd ng owrk ing time. Isolation valves should be used for safety during the maintenance and steam traps changing.

### Operation

Thermostatic steam traps operate according to the thermostatic attitude of a capsule which is placed into the trap. Capsule contains a special liquid inside which has lower vapourisation temperature than water. When the system starts up the cold condensate drops down the temperature of the capsule. Compressed capsule pushes the disc upward and discharges the condensate. With the increasing condensate temperature, liquid in the capsule starts vaporisation. Expanded capsule pushes the disc towards the seat and stops discharging.

### Installation:

TKK-41-42 can be installed both vertically and horizontally with the pipeline. Flow direction indicator arrow on the product body should be examined carefully. In case discharging of condensate into the atmosphere, temperature of the condensate which is around 100°C must be considered closely in order to maintain health and safety.

### Connection:

Screwed

### **Nominal Diameter:** DN10 (3/8") - DN15

(1/2") - DN20 (3/4") -DN25 (1")

# **Working Pressure:**

Up to 40 bar

### **Working Temperature:**

Up to 250°C

### Applications:

Steam jacket pipes Irons Ammonium releasers

### **Condensate Discharge Chart:**

### **Red Chart**

 $\Delta P$ = Condansate Discharge at the temperature which is max 10°C lower than steam saturation temperature.

### **Blue Chart**

 $\Delta P$ = Cold Condansate Discharge at 20°C.














PRODUCT FEATURES		
	Stainless Steel AISI 304	
	Stainless Steel AISI 316 (Opt.)	
Strainer, Seat	, Seat Stainless Steel AISI 304	
Thermosatic Capsule	ermosatic Capsule Hastelloy	
Connection Types	Threaded, Socket	


# TKK-41&42 THERMOSTATIC STEAM TRAPS














# DIMENSIONS





Size	Code	Thre	aded
Size	Code	ØD (mm)	ØH (mm)
3/8" -1"	TKK-41	55	42
1/4" -1"	TKK-42	65	42



All the dimensions in the table are given in "mm". Subject to technical alterations and deviations resulting from the manufacturing process without giving any notification.

	Part Name	Material
1	Body	Stainless Steel AISI 304 Opt.Stainless Steel AISI 316
2	Cover	Stainless Steel AISI 304 Opt.Stainless Steel AISI 316
3	Strainer Screen	Stainless Steel AISI 304
4	Thermostatic Capsule	Hastelloy



### **HEAD OFFICE - FACTORY**

Atatürk Sanayi Bölgesi Hadımköy Mahallesi Mustafa İnan Caddesi No: 44 Arnavutköy - İSTANBUL Tel: +90 212 771 01 45 (pbx) | Fax: +90 212 771 47 27 info@ayvaz.com | www.ayvaz.com

### Cona Caserta/Italy

Tel: +39 0823 187 3988 rmolaro@ayvaz.com

## Avvaz Germany Viernheim/Germany

Tel: +49 62046014399 germany@ayvaz.com

### Avvaz Ukraine Kiev/Ukraine Tel: +380 44 390 57 57

info@ayvaz.com.ua

### Tricorr Warsaw/Poland

Tel: +48 530 030 810 +48 533 603 335 tricorr@tricorr.eu

### Ayvaz Azerbaijan . Baku/Azerbaijan

Tel: +99 (455) 579-84-32 ahayatov@ayvaz.com

### Ayvaz Egypt Cairo/Egypt

Tel: +20 122 819 78 29 andrew.eid@ayvaz.com

Ayvaz	Gulf
Dubai/	U.A.E

+971 501306871 : mideast@ayvaz.com

#### : Ayvaz China Ningbo/China msahin@ayvaz.com

Avvaz Kazakhstan LLP : Almaty/Kazakhstan Tel: +7 (727) 327 97 57 info\_kz@ayvaz.com

Ayvaz N
Isperih/Bulgaria
Tel: +359 8431 27 32
office@ayvaz-n.eu

: Avvaz Serbia Belgrade/Serbia 32 Tel: +381 61 658 70 52 : yakbiyik@ayvaz.com : Tel: +84 89 8508345 : americas@ayvaz.com

### : Ayvaz Vietnam HCMC/Vietnam ggursoy@ayvaz.com

: Avvaz Americas Rhode Island/USA : Tel: +1 401 737 8380